

Hornbill

1000S & 2000S



Static Switch - 16 / 32 A

Single Phase

Special Features

- 32 bit DSP controlled design
- Automatic instantaneous transfer and retransfer without cross connection of sources
- Enhanced monitoring and diagnostics
- RS 232 or RS 485 interface with MODBUS protocol
- Redundant power supply
- 19" Rack mountable
- Complies with IEEE 446
- Natural air cooled for highest reliability



Technical Specifications - Hornbill 1000S & 2000S		
MODEL	Hornbill 1000S	Hornbill 2000S
Input / Output		
Nominal Voltage	110 / 115 / 230 / 240 V AC (1 Ph + N)	
Voltage Tolerances	+/- 15%	
Frequency Tolerances	wide band 40 - 70 Hz Auto Selectable	
Power Capacity	16A / 32A	
No. of Switching Poles	SINGLE	TWO
Overload Capacity	110% for 1 hour, 150% for 60 s, 200% for 10 s, 1000% for 100 ms	
Duty	Continuous	
Load Power Factor range	0.6 to unity leading or lagging	
Source Voltage Distortion	< 10% THD	
Controller	32 bit DSP	
Switch		
Transfer	< 5 ms in sync & < 15 ms in No sync	
Retransfer	< 5 ms in sync & not applicable for No sync	
Manual Bypass	Provided	
Efficiency (Ref. IEC 60146-1-1)*	≥ 99%	≥ 98%
Environmental		
Operating Temperature	0 to 40°C	
Storage Temperature	0 to 70°C	
Relative Humidity	Up to 95% (Non Condensing)	
Acoustic Noise @1 m (Ref. ISO 3746)	≤ 45 dBA	
Altitude	< 1000 meters above sea level (without de-rating) altitude	
Physical		
Enclosure Protection	IP – 20	
Cooling	Natural	
Color	RAL 7016	
Cable Entry	Back	
Dimensions	2 U (485 x 450 x 88.5 mm)	
Installation	19" Rack Mountable	
User Interface		
Indications	Source 1 Healthy, Source 1 Priority, Source 1 Feeding, Source 1 Manual bypass ON, Output ON	
	Source 2 Healthy, Source 2 Priority, Source 2 Feeding, Source 2 Manual bypass ON, No sync	
Fault Indication	Overload	
Standards	IEC 62310-1, IEEE 446	
Other Features	RS 485 MODBUS	

* At full load & nominal input voltage

► All specifications are subject to change ► Custom models available on request

Consul Neowatt Power Solutions Pvt Ltd
(CIN:U31900TN1985PTC011866)
119, 120, 120A, Electrical and Electronics Industrial Estate
Perungudi, Chennai - 600 096
Phone: +91 78100 09955
Website : www.consulindia.com
Email : enquiry@consulindia.com